

# REVTI ELECTRONICS INDUSTRIES

## CONTROL CABLE WITH COPPER CONDUCTOR PVC INSULATED & SHEATH ARMoured AND UNARMoured, VOLTAGE RATING 650 / 1100 V

Number of cores	Nominal Cross Section Area of Conductor Sq. mm	Nominal thickness of PVC insulation (mm)	Unarmored		Armored		
			Approx Overall Diameter mm	Approx Weight kg / km	Nominal Steel Armor Size mm W                  F	Approx Overall Diameter mm	Approx. Weight kg / km
2	1.5	0.8	12	150	1.4	13	350
3	1.5	0.8	12	175	1.4	14	390
4	1.5	0.8	13	200	1.4	15	425
5	1.5	0.8	13	240	1.4	16	485
6	1.5	0.8	14	257	1.4	16	545
7	1.5	0.8	14	285	1.4	16	555
8	1.5	0.8	15	330	1.4	17	625
9	1.5	0.8	16	375	1.4	18	690
10	1.5	0.8	17	390	1.4	20	740
12	1.5	0.8	18	435	4x0.8	19	640
14	1.5	0.8	19	490	4x0.8	20	730
16	1.5	0.8	20	540	4x0.8	21	790
19	1.5	0.8	21	630	4x0.8	22	880
24	1.5	0.8	24	775	4x0.8	25	1070
27	1.5	0.8	24	845	4x0.8	26	1160
30	1.5	0.8	25	920	4x0.8	27	1235
33	1.5	0.8	26	990	4x0.8	27	1340
37	1.5	0.8	27	1090	4x0.8	28	1430
44	1.5	0.8	30	1275	4x0.8	32	1685
48	1.5	0.8	31	1390	4x0.8	32	1800
52	1.5	0.8	32	1500	4x0.8	33	1895
56	1.5	0.8	33	1600	4x0.8	34	2015
61	1.5	0.8	34	1710	4x0.8	35	2150
2	2.5	0.9	13	190	1.4	15	420
3	2.5	0.9	13	230	1.4	15	465
4	2.5	0.9	14	275	1.4	16	525
5	2.5	0.9	15	320	1.4	17	600
6	2.5	0.9	16	375	1.4	18	685
7	2.5	0.9	16	390	1.4	18	705
8	2.5	0.9	17	460	1.4	20	810
9	2.5	0.9	18	520	4x0.8	20	765
10	2.5	0.9	20	540	4x0.8	22	810
12	2.5	0.9	21	630	4x0.8	22	880
14	2.5	0.9	22	710	4x0.8	23	980
16	2.5	0.9	23	790	4x0.8	24	1060
19	2.5	0.9	24	895	4x0.8	25	1190
24	2.5	0.9	28	1110	4x0.8	29	1485
27	2.5	0.9	28	1210	4x0.8	29	1575
30	2.5	0.9	29	1325	4x0.8	31	1735
33	2.5	0.9	30	1440	4x0.8	32	1850
37	2.5	0.9	32	1620	4x0.8	33	2010
44	2.5	0.9	36	1900	4x0.8	37	2365
48	2.5	0.9	36	2040	4x0.8	37	2500
52	2.5	0.9	37	2190	4x0.8	38	2670
56	2.5	0.9	38	2335	4x0.8	39	2840
61	2.5	0.9	39	2500	4x0.8	40	3010